


Internet Sales Office

Toll Free: (800) 238-9080

Toll Free Fax: (877) 608-0597

<http://www.damarww.com>[-Click to Print-](#)You are here: [Home](#) > [Ballasts](#) > [Fluorescent Sign Ballasts](#) > 06244H**ITEM#:** 06244H

Additional Images

[Photo #2](#) [Photo #3](#) [Spec Image](#) [Wiring Diagram](#)
Item#: 06244H**Industry Desc.:** ESB-0432-14-120/277HF**Friendly Desc.:** ELEC. SIGN BALLAST 120-277**Volts:** 120/277**Ballast Type:** Electronic**Start Method:** Instant Start**Package Qty:** 1**Case Qty:** 10

Additional Info: High power factor - instant start.
 Class P, Type 2 Outdoor , No PCB's, Sound Rating: Class A
 Minimum starting Temperature -20° F, -30° C
 Maximum Case Temperature: 194F or 90C
 Open Circuit Voltage: 800V, Less than 600V to ground
 Inherent thermal protection
 Install in accordance with National Electrical Code
 For 4,3,2 and 1 T12HO lamps up to 8ft long or any combination thereof from 4-32ft
 For 4,3,2 and 1 T8HO lamps up to 6ft long or any combination thereof from 4-24ft.

Copyright 1999-2012 Damar® Worldwide. All rights reserved.